

2500 SERIES · FLOOR · WALL · CEILING

Oak Sand Grey Universal

2500 Plank 1-Strip 180 2V · Article 548 125

A sandy, soft grey with gentle warmth and natural texture.

DESIGN	Oak Sand Grey Universal
FORMAT	2500 Plank 1-Strip 180 2V
DIMENSIONS	12/2.5 × 180 × 2200 mm
SURFACE / FINISH	naturaDur · Universal
TONE FAMILY	Greige
COLLECTION	HARO PARQUET 2500 (EN 13489:2017)
APPLICATION	Floor · Wall · Ceiling
CONSTRUCTION	3-layer · ≥ 2.5 mm oak top layer · spruce core
INSTALLATION	Top Connect® floating / direct stick · mechanical or adhesive on walls & ceilings
UNDERFLOOR HEATING	0.113 m²K/W (floor use)
FIRE & SLIP	Cfl-s1 / Dfl-s1 · R9/R10
WARRANTY	15-year residential (floor use)
CERTIFICATION	100% PEFC · Blue Angel · CE · Made in Germany

MADE IN GERMANY 100% PEFC CFL-S1 · R10 15-YEAR RESIDENTIAL WARRANTY

HARO FLOORING AUSTRALIA sales@haroflooring.com.au · +61 473 011 887 · haroflooring.com.au 2026 Collection · Issue 2026.07

Product imagery and data verified against haro.com, July 2026. Full technical documentation — installation, warranty, care, DoP, EPD and certificates — at haroflooring.com.au/catalogues.