

HARO

AUSTRALIA



LIVING BY HARO · TRITTY LAMINATE

Laminate.

German-made laminate with authentic oak decors, Top Connect installation and a 25-year residential warranty on Tritty 100.

2024-25 COLLECTION

LIVING BY HARO

The look of oak. The ease of laminate.

HARO's Tritty laminate ranges bring authentic oak decors to busy Australian homes – with the durability, easy care and value that laminate does best.

Every board is made in Rosenheim, Germany, to the same standards as HARO's engineered timber: authentically textured decors, precise Top Connect click installation and certified healthy-home credentials – Blue Angel, A+ emissions class and EPLF membership.

Tritty 100 is the classic, rated AC4 for use class 23/32. Tritty 200 adds length and width on a 2-metre board. Tritty 200 Aqua steps up to AC6 and use class 23/33, with an AquaReject moisture-control core for kitchens and laundries.

Checked for Australian conditions by our local team – UV-stable finishes, movement behaviour across humidity swings from Brisbane to Hobart, underfloor-heating compatibility, and radiant-flux fire data for Australian specification.

MADE IN GERMANY BLUE ANGEL A+ EMISSIONS EPLF



THE SYSTEM

Built for real life.

01 AUTHENTIC SURFACE

Specially impregnated overlay and decorative laminate, textured to follow the grain — convincingly natural underfoot and to the eye.

02 ENGINEERED CORE BOARD

A dense, dimensionally stable core; Tritty 200 Aqua uses HARO's moisture-controlling AquaReject board.

03 TOP CONNECT®

HARO's patented glueless click system — angle in, press, finished. Floating installation over HARO underlay.

04 PROVEN HARD-WEARING

Abrasion class AC4 (Tritty 100) to AC6 (Tritty 200 Aqua) · impact-tested · stain resistance class 5 (EN 438-2).

05 HEALTHY LIVING

Blue Angel certified · A+ emissions class · formaldehyde and plasticiser controlled to the strictest European limits.

06 UNDERFLOOR HEATING

Thermal resistance just 0.065 m²K/W — excellent heat transfer on modern hydronic systems.



THE COLLECTION

Tritty 100 — the classic.



Oak Eleganza Crème White

TRITTY 100 · PLANK 1-STRIP · AC4

A light, elegant crème white with fine, even graining.
Calm and contemporary – brightness without glare.



Oak Eleganza Puro

TRITTY 100 · PLANK 1-STRIP · AC4

Pure, natural oak decor with a refined, even character.
The quiet all-rounder that lets the room speak.



Oak Italica Crème

TRITTY 100 · PLANK 1-STRIP · AC4

Soft crème tones with gentle Mediterranean warmth.
Sunlit and easy to live with.



Oak Sicilia

TRITTY 100 · PLANK 1-STRIP · AC4

Balanced natural oak in an authentic matt texture. The
versatile heart of the range.

Decors are authentic wood reproductions; swatches show official HARO decor imagery where available. Confirm with physical samples.

THE COLLECTION

Tritty 200 & 200 Aqua.



Oak Veneto Honey

TRITTY 200 · LONG-FORMAT PLANK

Warm honey tones on a long, wide 243 mm board.
Golden warmth with generous scale.



Oak Veneto Mocca

TRITTY 200 · LONG-FORMAT PLANK

Rich mocca depth in an authentic matt texture.
Grounded, warm and quietly luxurious.



Oak Veneto Sand

TRITTY 200 · LONG-FORMAT PLANK

A soft greige between sand and stone. Light, modern
and forgiving in busy households.



Oak Portland Puro Aqua

TRITTY 200 AQUA · AC6 · WATER-RESISTANT

Grey oak decor over the AquaReject moisture-control
core. Made for kitchens, laundries and moisture-prone
rooms.

Decors are authentic wood reproductions; swatches show official HARO decor imagery where available. Confirm with physical samples.

TECHNICAL DATA

The detail beneath the beauty.

COLLECTIONS	Tritty 100 · Tritty 200 · Tritty 200 Aqua (EN 13329)
DIMENSIONS	Tritty 100: 8 × 193 × 1282 mm · Tritty 200 / 200 Aqua: 8 × 243 × 2000 mm
FORMAT	Plank 1-Strip · 4-sided bevel (4V) · authentic textured matt
USE CLASS	Tritty 100: 23/32 (residential intensive / commercial general) · Tritty 200 Aqua: 23/33 (commercial heavy)
ABRASION RESISTANCE	Tritty 100: AC4 · Tritty 200 Aqua: AC6 (EN 13329)
WATER RESISTANCE	Tritty 200 Aqua: AquaReject core · thickness swelling $\leq 8\%$ (standard allows 15%)
INSTALLATION	Top Connect® click system · floating over HARO underlay
FIRE & SLIP	C _{fl} -s1 (EN 13501-1) · sliding friction DS / R9 (EN 14041; EN 13893)
UNDERFLOOR HEATING	Thermal resistance 0.065 m ² K/W — compatible with modern systems
EMISSIONS & HEALTH	Blue Angel · A+ emissions class · stain resistance class 5 (EN 438-2)
QUALITY STANDARD	EPLF member manufacturer · Made in Germany
WARRANTY	Tritty 100 — 25-year residential · Tritty 200 Aqua — HARO Aqua residential warranty · commercial terms available

Values per Hamberger Flooring data sheets TDB 502 (Tritty 100) and TDB 524 (Tritty 200 Aqua) and HARO laminate warranty terms. Full data sheets, DoP and EPD at haroflooring.com.au.

HARO

German laminate, naturally at home.

ENQUIRIES

sales@haroflooring.com.au

PHONE

+61 473 011 887

ONLINE

haroflooring.com.au



MADE IN GERMANY BLUE ANGEL A+ EMISSIONS EPLF

HARO Flooring Australia — exclusive Australian distributor of HARO, made by Hamberger Flooring GmbH & Co. KG, Rosenheim, Germany.
Samples, technical documentation and specification support available on request. Colours are indicative; confirm with physical samples. 2024-25
Collection · Issue 2026.07 · © 2026 HARO Flooring Australia.