

HARO

AUSTRALIA

2500 SERIES · FLOOR · WALL · CEILING

Walls & Ceilings.

One timber language for the whole room. German-made oak panelling that carries the same natural tone across floor, wall and ceiling.

2024-25 COLLECTION

THE COMPLETE ROOM

A room doesn't stop at the floor.

HARO's 2500 Series lets you bring the same natural timber across walls and ceilings — a complete room concept in perfectly matched tones and textures.

Lightweight, pre-finished and quick to install, each board turns an ordinary surface into a defining architectural feature — from a single accent wall to a fully clad room.

Specify floor and panelling together for a seamless, enveloping effect. Stairs, skirtings and profiles complete the look in the same timber.

Every board is made by Hamberger Flooring in Rosenheim, Germany — a family company and Germany's leading parquet manufacturer, now in its fifth generation.



THE SYSTEM

Real oak. Engineered to behave.

01 SURFACE – NATURADUR / NATURALIN PLUS

Four designs carry naturaDur natural matt – pre-finished protection with easy care. Four are finished in naturaLin plus natural oil for a breathing, close-to-nature surface.

02 TOP LAYER – ≥ 2.5 MM EUROPEAN OAK

Precious-wood wear layer, brushed for texture. On floors it can be sanded, with a 15-year residential warranty.

03 MIDDLE LAYER – SOLID SPRUCE FINGERSTRIPS

Labour-intensive to manufacture, and the reason a HARO board stays flat and stable for life.

04 BACKING – SOFTWOOD VENEER

A stabilising counter-veneer that further increases dimensional stability.

05 JOINT – TOP CONNECT®

HARO's patented glueless locking system: angle-in on the long side, Top Connect 5G on the short side. Easy, perfect-fit, permanent.

06 ONE BOARD, THREE PLANES

The same 12 × 180 × 2200 mm board installs as flooring, wall cladding or ceiling lining – one tone, every surface.



2500 SERIES – FLOOR AND PANELLING IN ONE LANGUAGE

Eight tones of European oak.



Oak Alabama

537 552

ALABAMA · BRUSHED · NATURALIN PLUS OIL

A warm, characterful oak with relaxed, natural movement. The Alabama grade celebrates knots and life in the grain.



Oak Universal

548 127

UNIVERSAL · BRUSHED · NATURADUR

Natural, balanced oak — the most versatile tone for a complete room in one timber.



Oak Invisible Universal

548 126

UNIVERSAL · BRUSHED · NATURADUR

An invisible matt finish that looks and feels untreated — raw oak, fully protected.



Oak Light White Universal

548 123

UNIVERSAL · BRUSHED · NATURADUR

A soft, light white that brings calm, airy warmth across floor, wall and ceiling.

THE COLLECTION

One tone. Every surface.



Oak Puro White
Universal

537 548

UNIVERSAL · BRUSHED · NATURALIN PLUS OIL

Pure white over natural oak — bright, contemporary and clean.



Oak Puro White
Alabama

537 549

ALABAMA · BRUSHED · NATURALIN PLUS OIL

Pure white with relaxed Alabama character — light, textured and quietly expressive.



Oak Sand Grey
Universal

548 125

UNIVERSAL · BRUSHED · NATURADUR

A sandy, soft grey with gentle warmth and natural texture.



Oak Velvet Brown
Universal

539 943

UNIVERSAL · BRUSHED · NATURALIN PLUS OIL

A deep, velvety brown rich with warmth and depth.

Swatches are official HARO decor imagery. Confirm colour with physical samples.

TECHNICAL DATA

The detail beneath the beauty.

COLLECTION	HARO PARQUET 2500 Series — Plank 1-Strip 2V (EN 13489:2017)
APPLICATION	Floor · Wall · Ceiling
DIMENSIONS	12/2.5 × 180 × 2200 mm
TOP LAYER	≥ 2.5 mm European oak, brushed
CONSTRUCTION	3-layer: oak top layer · solid spruce fingerstrip core · softwood backing veneer
SURFACE FINISH	naturaDur natural matt or naturaLin plus natural oil, by design — see each design's data sheet
INSTALLATION SYSTEM	Top Connect® glueless locking — angle-in long side, Top Connect 5G short side
INSTALLATION METHODS	Floating or direct stick (floor) · mechanical fix / adhesive (wall & ceiling)
MOISTURE BEHAVIOUR	Equilibrium humidity 7.5% at 23°C / 50% RH (EN 13183-1)
UNDERFLOOR HEATING	Compatible — thermal resistance 0.113 m ² K/W
FIRE & SLIP	C _{fl} -s1 / D _{fl} -s1 (EN 13501-1) · slip R9/R10 (EN 13893) · castor chair DIN EN 425
EMISSIONS & HEALTH	Formaldehyde ≤ 0.05 ppm (EN 717-1) · VOC ≤ 300 ppm · plasticiser-free · A+
CERTIFICATION	100% PEFC · Blue Angel · CE · Made in Germany
WARRANTY	Residential — 15 years (layer structure & lamination, floor use)

Values per Hamberger Flooring data sheet TDB 146 (HARO PARQUET 2500) and article-specific specification sheets. Full test reports available from HARO Flooring Australia.

HARO

Naturally beautiful — floor, wall
and ceiling.

ENQUIRIES

sales@haroflooring.com.au

PHONE

+61 473 011 887

ONLINE

haroflooring.com.au



MADE IN GERMANY 100% PEFC BLUE ANGEL 150 YEARS

HARO Flooring Australia — exclusive Australian distributor of HARO, made by Hamberger Flooring GmbH & Co. KG, Rosenheim, Germany.
Samples, technical documentation and specification support available on request. Colours are indicative; confirm with physical samples. 2024-25
Collection · Issue 2026.07 · © 2026 HARO Flooring Australia.